



VI-111

Item No	Tire Size	PR	LR	LI	SR	Rim	S.W.		O.D.		Max. Load				Max Pressure				Tread Depth		Weight		Road Condition	Pattern
							in	mm	in	mm	Single		Dual		Single		Dual		32nd	mm	lbs	kg		
											lbs	kg	lbs	kg	psi	kpa	psi	kpa						
	11R22.5	14	G	144/142	M	8,3	11,0	279	41,5	1054	6175	2800	5840	2650	105	720	105	720	19,0	15,0	110,2	50	M+S	VI-111
HF-TBR93	11R22.5	16	H	146/143	L	8,3	11,0	279	41,5	1054	6610	3000	6005	2725	120	830	120	830	19,0	15,0	110,2	50	M+S	VI-111
HF-TBR96	11R24.5	14	G	146/143	M	8,3	11,0	279	43,5	1104	6610	3000	6005	2725	105	720	105	720	19,0	15,0	119,1	54	M+S	VI-111
HF-TBR97	11R24.5	16	H	149/146	L	8,3	11,0	279	43,5	1104	7160	3250	6610	3000	120	830	120	830	19,0	15,0	119,1	54	M+S	VI-111
HF-TBR86	215/75R17.5	16	H	135/133	M	6,0	8,4	212	30,2	767	4806	2180	4542	2060	123	850	125	850	15,0	12,0	56,2	25,5	M+S	VI-111
HF-TBR87	235/75R17.5	16	H	132/130	M	6,8	9,2	233	31,4	797	6008	2725	5677	2575	127	875	127	875	19,0	15,0	63,9	29	M+S	VI-111
HF-TBR88	225/70R19.5	14	G	128/126	L	6,8	8,9	226	31,9	811	3970	1800	3750	1700	110	760	110	760	16,5	13,0	62,8	28,5	M+S	VI-111
HF-TBR89	245/70R19.5	16	H	135/133	M	7,5	9,8	248	33,0	839	4806	2180	4542	2060	120	830	120	830	16,5	13,0			M+S	VI-111
HF-TBR90	255/70R22.5	16	H	140/137	L	7,5	10,1	255	36,6	930	5510	2500	5070	2300	120	830	120	830	16,5	13,0	84,9	38,5	M+S	VI-111
HF-TBR91	295/75R22.5	14	G	144/141	M	9,0	11,7	298	39,9	1014	6175	2800	5677	2575	110	760	110	760	20,0	15,5	108,0	49	M+S	VI-111
HF-TBR92	295/75R22.5	16	H	146/143	L	9,0	11,7	298	39,9	1014	6610	3000	6005	2725	120	830	120	830	20,0	15,5	108,0	49	M+S	VI-111
HF-TBR94	285/75R24.5	14	G	144/141	M	8,3	11,1	283	41,3	1050	6175	2800	5680	2575	110	760	110	760	20,0	15,5	111,3	50,5	M+S	VI-111
HF-TBR95	285/75R24.5	16	H	147/144	L	8,3	11,1	283	41,3	1050	6779	3075	6175	2800	120	830	120	830	20,0	15,5	111,3	50,5	M+S	VI-111



VI-312

Item No	Tire Size	PR	LR	LI	SR	Rim	S.W.		O.D.		Max. Load				Max Pressure				Tread Depth		Weight		Road Condition	Pattern
							in	mm	in	mm	Single		Dual		Single		Dual		32nd	mm	lbs	kg		
											lbs	kg	lbs	kg	psi	kpa	psi	kpa						
	11R22.5	14	G	144/142	M	8,3	11,0	279	41,7	1054	6175	2800	5840	2650	105	720	105	720	27,0	21,5	121,3	55	M+S	VI-312
HF-TBR100	11R22.5	16	H	146/143	L	8,3	11,0	279	41,7	1054	6610	3000	6005	2725	120	830	120	830	27,0	21,5	121,3	55	M+S	VI-312
HF-TBR103	11R24.5	14	G	146/143	M	8,3	11,0	279	43,5	1104	6610	3000	6005	2725	105	720	105	720	27,0	21,5	132,3	60	M+S	VI-312
HF-TBR104	11R24.5	16	H	149/146	L	8,3	11,0	279	43,5	1104	7160	3250	6610	3000	120	830	120	830	27,0	21,5	132,3	60	M+S	VI-312
HF-TBR98	295/75R22.5	14	G	144/141	M	9,0	11,7	298	40,2	1020	6175	2800	5680	2575	110	760	110	760	28,0	22,0	118,0	53,5	M+S	VI-312
HF-TBR99	295/75R22.5	16	H	146/143	L	9,0	11,7	298	40,2	1020	6610	3000	6005	2725	120	830	120	830	28,0	22,0	118,0	53,5	M+S	VI-312
HF-TBR101	285/75R24.5	14	G	144/141	M	8,3	11,1	283	41,6	1056	6175	2800	5680	2575	110	760	110	760	28,0	22,0	121,9	55,3	M+S	VI-312
HF-TBR102	285/75R24.5	16	H	147/144	L	8,3	11,1	283	41,6	1056	6779	3075	6175	2800	120	830	120	830	28,0	22,0	121,9	55,3	M+S	VI-312